

# 3M™ PELTOR™ WorkTunes™ Pro Headset



## Hearing protection that rocks!

You don't have to choose between protecting your hearing and listening to your favourite music whilst at work. The WorkTunes Pro headset's built in antenna, fast digital tuning and ability to store stations makes it flexible and easy to work with, without sacrificing protection. When you enjoy your work you can get more done, faster and better.



Built-in  
AM/FM  
radio

Hearing protection with  
built-in AM/FM radio



External  
audio  
input

Connect to your mobile  
phone or similar device  
with the 3.5mm jack

## Features and benefits

### Attachments

To fit most users needs, the headset is available in both headband and helmet attachment. All in black colour.

### Dual shell design

To protect the electronics from sweat inside the cup, all electronics are placed on the outside beneath the shell.

### Large user-friendly push buttons

Voice guided menu system:

- ▶ Volume (8 steps)
- ▶ Search station  
(announced frequencies)
- ▶ Store station (up to 5 stations)
- ▶ Radio band

### 3.5 mm jack

A listen-only stereo input to connect to a cell-phone, radio, two-way radio or other external devices (limited to a safe noise level).

### Stainless steel wire headband

Wire headband offers comfortable and consistent pressure.

### Built-in antenna

To avoid snags.

### 2xAA batteries

Lasting for approx. 40hrs of use. The headset will turn off after 4hrs of non-use to save batteries. A message will be heard when the battery is low.

### Replaceable cushions and foam liners (hygiene kit)

### Hearing protection

Noise attenuating ear cups help provide hearing protection in environments with potentially hazardous noise.



# Attenuation values

HRXS221A - Headband							EN 352-1:2002	
Frequency (Hz)	125	250	500	1000	2000	4000	8000	
Mf (dB)	17.0	24.0	29.5	36.9	37.3	39.3	35.4	
sf (dB)	3.2	2.0	2.6	3.3	4.9	3.2	3.9	
APVf (dB)	13.8	22.0	26.9	33.6	32.4	36.1	31.5	

SNR = 32dB. H = 34dB. M = 29dB. L = 22dB.

HRXS221P3E - Helmet Attachment							EN 352-1:2002	
Frequency (Hz)	125	250	500	1000	2000	4000	8000	
Mf (dB)	16.6	22.0	29.1	36.3	36.4	38.7	34.2	
sf (dB)	2.7	2.2	2.9	3.4	3.9	4.2	4.0	
APVf (dB)	13.9	19.8	26.2	32.9	32.5	34.5	30.2	

SNR = 31dB. H = 33dB. M = 28dB. L = 21dB.

## Ordering information

Part Number	Description
HRXS221A	WorkTunes™ Pro AM/FM Radio Headset, black, headband
HRXS221P3E	WorkTunes™ Pro AM/FM Radio Headset, black, helmet attachment
Accessories	
HY220	HY220 Hygiene kit
HY100A	HY100A clean hygiene pad

### Personal Safety Division

3M United Kingdom PLC  
3M Centre, Cain Road, Bracknell  
Berkshire RG12 8HT  
t: 0870 60 800 60  
www.3M.co.uk/safety

3M Ireland Limited  
The Iveagh Building  
The Park  
Carrickmines  
Dublin 18

Please recycle. Printed in the UK. © 3M 2018. 3M, PELTOR and WorkTunes are trademarks of the 3M company. Used under licence by 3M subsidiaries and affiliates. All rights reserved. J436522