

PRODUCT CODE: PAF-0077

PRODUCT NAME: CleanSpace™ Combined Filter A2 TM3 P SL R



Description

The CleanSpace Combined Filter A2 TM3 P SL R is suitable for protection against airborne particulate (dust, mists and fumes), organic gases or vapours (boiling point >65C).
IMPORTANT: When selecting a CleanSpace Filter please consult a Health and Safety specialist for advice on the appropriate respiratory equipment and filter use.

Approvals

Compatible with ALL CleanSpace PAPR Power Units

Standard
EN 12942

Classification
PAPR-P3

Features

- The CleanSpace A2 TM3 Filter must be used in conjunction with the CleanSpace Filter Adaptor (PAF-0038)
- Used with the revolutionary CleanSpace PAPR: light weight, no hoses or belts
- Suitable for protection against airborne particulate (dust, mists and fumes), organic gases or vapours (boiling point >65C)
- Materials: Fibreglass particulate media, activated carbon and plastic casing, silicone seal
- Easily fitted and removed from the power unit

Specifications and materials

- Weight: average 220g. Dimensions: 170mm x 40mm x 70mm
- Packaged Shelf life: 3 years from manufacturing date.
- Storage and Use: -10°C to +55°C (-4°F to +131°F) at <90% relative humidity. Store away from direct sunlight, grease and oil
- Only to be used with CleanSpace PAPR Power Units
- These filters are not water proof and should be replaced if in contact with water

Suitable Applications

Mining, Welding, Manufacturing, Smelting, Construction, Recycling Plants, Emergency Services, Agriculture, Processing Plants, Grinding
Refer to Filter Selection Table for more details:
<http://www.cleanspacetechnology.com/wp-content/uploads/2016/09/CleanSpace-Filter-Selection-Table-ENG-V2-web.pdf>.

Training

Online training available with verification for compliance purposes.
Contact sales@paftec.com.

Limitations

CleanSpace respirators are air filtering, fan assisted positive pressure masks and designed to be worn in environments where there is sufficient oxygen to breathe safely. Do not use the CleanSpace in IDLH atmospheres, to protect against gases/vapours that cannot be filtered, or in Oxygen enriched or deficient atmospheres.